

TABLE OF CONTENTS

<u>Section</u>	<u>Title</u>	<u>Page</u>
CHAPTER 15 ACCIDENT ANALYSES.....		15.0-1
15.0.1	Classification of Plant Conditions.....	15.0-1
15.0.1.1	Condition I: Normal Operation and Operational Transients	15.0-1
15.0.1.2	Condition II: Faults of Moderate Frequency.....	15.0-2
15.0.1.3	Condition III: Infrequent Faults.....	15.0-3
15.0.1.4	Condition IV: Limiting Faults	15.0-4
15.0.2	Optimization of Control Systems	15.0-5
15.0.3	Plant Characteristics and Initial Conditions Assumed in the Accident Analyses	15.0-5
15.0.3.1	Design Plant Conditions	15.0-5
15.0.3.2	Initial Conditions	15.0-5
15.0.3.3	Power Distribution	15.0-6
15.0.4	Reactivity Coefficients Assumed in the Accident Analysis	15.0-7
15.0.5	Rod Cluster Control Assembly Insertion Characteristics	15.0-7
15.0.6	Protection and Safety Monitoring System Setpoints and Time Delays to Trip Assumed in Accident Analyses.....	15.0-8
15.0.7	Instrumentation Drift and Calorimetric Errors, Power Range Neutron Flux.....	15.0-8
15.0.8	Plant Systems and Components Available for Mitigation of Accident Effects.....	15.0-9
15.0.9	Fission Product Inventories.....	15.0-9
15.0.10	Residual Decay Heat.....	15.0-9
15.0.10.1	Total Residual Heat.....	15.0-9
15.0.10.2	Distribution of Decay Heat Following a Loss-of-Coolant Accident.....	15.0-9
15.0.11	Computer Codes Used	15.0-10
15.0.11.1	FACTRAN Computer Code	15.0-10
15.0.11.2	LOFTRAN Computer Code	15.0-10
15.0.11.3	TWINKLE Computer Code	15.0-11
15.0.11.4	VIPRE-01 Computer Code.....	15.0-12
15.0.11.5	COAST Computer Program	15.0-12
15.0.12	Component Failures	15.0-12
15.0.12.1	Active Failures	15.0-12
15.0.12.2	Passive Failures	15.0-13
15.0.12.3	Limiting Single Failures	15.0-13
15.0.13	Operator Actions	15.0-13
15.0.14	Loss of Offsite ac Power	15.0-13
15.0.15	Combined License Information.....	15.0-14
15.0.16	References.....	15.0-15

TABLE OF CONTENTS (Cont.)

<u>Section</u>	<u>Title</u>	<u>Page</u>
15.1	Increase in Heat Removal From the Primary System	15.1-1
15.1.1	Feedwater System Malfunctions that Result in a Decrease in Feedwater Temperature	15.1-1
15.1.1.1	Identification of Causes and Accident Description.....	15.1-1
15.1.1.2	Analysis of Effects and Consequences	15.1-2
15.1.1.3	Conclusions	15.1-2
15.1.2	Feedwater System Malfunctions that Result in an Increase in Feedwater Flow.....	15.1-2
15.1.2.1	Identification of Causes and Accident Description.....	15.1-2
15.1.2.2	Analysis of Effects and Consequences	15.1-3
15.1.2.3	Conclusions	15.1-6
15.1.3	Excessive Increase in Secondary Steam Flow.....	15.1-6
15.1.3.1	Identification of Causes and Accident Description.....	15.1-6
15.1.3.2	Analysis of Effects and Consequences	15.1-7
15.1.3.3	Conclusions	15.1-9
15.1.4	Inadvertent Opening of a Steam Generator Relief or Safety Valve.....	15.1-9
15.1.4.1	Identification of Causes and Accident Description.....	15.1-9
15.1.4.2	Analysis of Effects and Consequences	15.1-10
15.1.4.3	Margin to Critical Heat Flux	15.1-12
15.1.4.4	Conclusions	15.1-12
15.1.5	Steam System Piping Failure	15.1-12
15.1.5.1	Identification of Causes and Accident Description.....	15.1-12
15.1.5.2	Analysis of Effects and Consequences	15.1-14
15.1.5.3	Conclusions	15.1-18
15.1.5.4	Radiological Consequences.....	15.1-18
15.1.6	Inadvertent Operation of the PRHR Heat Exchanger.....	15.1-20
15.1.6.1	Identification of Causes and Accident Description.....	15.1-20
15.1.6.2	Analysis of Effects and Consequences	15.1-21
15.1.6.3	Conclusions	15.1-24
15.1.7	Combined License Information.....	15.1-24
15.1.8	References.....	15.1-24
15.2	Decrease in Heat Removal by the Secondary System.....	15.2-1
15.2.1	Steam Pressure Regulator Malfunction or Failure that Results in Decreasing Steam Flow	15.2-1
15.2.2	Loss of External Electrical Load	15.2-1
15.2.2.1	Identification of Causes and Accident Description.....	15.2-1
15.2.2.2	Analysis of Effects and Consequences	15.2-3
15.2.2.3	Conclusions	15.2-3
15.2.3	Turbine Trip.....	15.2-3
15.2.3.1	Identification of Causes and Accident Description.....	15.2-3
15.2.3.2	Analysis of Effects and Consequences	15.2-4
15.2.3.3	Conclusions	15.2-8

TABLE OF CONTENTS (Cont.)

<u>Section</u>	<u>Title</u>	<u>Page</u>
	15.2.4 Inadvertent Closure of Main Steam Isolation Valves.....	15.2-8
	15.2.5 Loss of Condenser Vacuum and Other Events Resulting in Turbine Trip.....	15.2-8
	15.2.6 Loss of ac Power to the Plant Auxiliaries	15.2-9
	15.2.6.1 Identification of Causes and Accident Description.....	15.2-9
	15.2.6.2 Analysis of Effects and Consequences	15.2-10
	15.2.6.3 Conclusions	15.2-12
	15.2.7 Loss of Normal Feedwater Flow	15.2-13
	15.2.7.1 Identification of Causes and Accident Description.....	15.2-13
	15.2.7.2 Analysis of Effects and Consequences	15.2-14
	15.2.7.3 Conclusions	15.2-16
	15.2.8 Feedwater System Pipe Break.....	15.2-16
	15.2.8.1 Identification of Causes and Accident Description.....	15.2-16
	15.2.8.2 Analysis of Effects and Consequences	15.2-18
	15.2.8.3 Conclusions	15.2-20
	15.2.9 Combined License Information.....	15.2-21
	15.2.10 References.....	15.2-21
15.3	Decrease in Reactor Coolant System Flow Rate	15.3-1
	15.3.1 Partial Loss of Forced Reactor Coolant Flow	15.3-1
	15.3.1.1 Identification of Causes and Accident Description.....	15.3-1
	15.3.1.2 Analysis of Effects and Consequences	15.3-2
	15.3.1.3 Conclusions	15.3-3
	15.3.2 Complete Loss of Forced Reactor Coolant Flow	15.3-3
	15.3.2.1 Identification of Causes and Accident Description.....	15.3-3
	15.3.2.2 Analysis of Effects and Consequences	15.3-4
	15.3.2.3 Conclusions	15.3-5
	15.3.3 Reactor Coolant Pump Shaft Seizure (Locked Rotor).....	15.3-5
	15.3.3.1 Identification of Causes and Accident Description.....	15.3-5
	15.3.3.2 Analysis of Effects and Consequences	15.3-5
	15.3.3.3 Radiological Consequences.....	15.3-8
	15.3.4 Reactor Coolant Pump Shaft Break	15.3-10
	15.3.4.1 Identification of Causes and Accident Description.....	15.3-10
	15.3.4.2 Conclusion.....	15.3-10
	15.3.5 Combined License Information.....	15.3-10
	15.3.6 References.....	15.3-10
15.4	Reactivity and Power Distribution Anomalies	15.4-1
	15.4.1 Uncontrolled Rod Cluster Control Assembly Bank Withdrawal from a Subcritical or Low-power Startup Condition.....	15.4-1
	15.4.1.1 Identification of Causes and Accident Description.....	15.4-1
	15.4.1.2 Analysis of Effects and Consequences	15.4-3
	15.4.1.3 Conclusions	15.4-5

TABLE OF CONTENTS (Cont.)

<u>Section</u>	<u>Title</u>	<u>Page</u>
15.4.2	Uncontrolled Rod Cluster Control Assembly Bank Withdrawal at Power	15.4-5
15.4.2.1	Identification of Causes and Accident Description.....	15.4-5
15.4.2.2	Analysis of Effects and Consequences	15.4-7
15.4.2.3	Conclusions	15.4-11
15.4.3	Rod Cluster Control Assembly Misalignment (System Malfunction or Operator Error)	15.4-12
15.4.3.1	Identification of Causes and Accident Description.....	15.4-12
15.4.3.2	Analysis of Effects and Consequences	15.4-14
15.4.3.3	Conclusions	15.4-17
15.4.4	Startup of an Inactive Reactor Coolant Pump at an Incorrect Temperature	15.4-17
15.4.5	A Malfunction or Failure of the Flow Controller in a Boiling Water Reactor Loop that Results in an Increased Reactor Coolant Flow Rate	15.4-17
15.4.6	Chemical and Volume Control System Malfunction that Results in a Decrease in the Boron Concentration in the Reactor Coolant	15.4-17
15.4.6.1	Identification of Causes and Accident Description.....	15.4-17
15.4.6.2	Analysis of Effects and Consequences	15.4-19
15.4.6.3	Conclusions	15.4-25
15.4.7	Inadvertent Loading and Operation of a Fuel Assembly in an Improper Position	15.4-25
15.4.7.1	Identification of Causes and Accident Description.....	15.4-25
15.4.7.2	Analysis of Effects and Consequences	15.4-26
15.4.7.3	Conclusions	15.4-26
15.4.8	Spectrum of Rod Cluster Control Assembly Ejection Accidents	15.4-27
15.4.8.1	Identification of Causes and Accident Description.....	15.4-27
15.4.8.2	Analysis of Effects and Consequences	15.4-30
15.4.8.3	Radiological Consequences	15.4-35
15.4.9	Combined License Information.....	15.4-38
15.4.10	References.....	15.4-38
15.5	Increase in Reactor Coolant Inventory	15.5-1
15.5.1	Inadvertent Operation of the Core Makeup Tanks During Power Operation	15.5-1
15.5.1.1	Identification of the Causes and Accident Description.....	15.5-1
15.5.1.2	Analysis of Effects and Consequences	15.5-2
15.5.1.3	Results	15.5-4
15.5.1.4	Conclusions	15.5-5
15.5.2	Chemical and Volume Control System Malfunction That Increases Reactor Coolant Inventory	15.5-5
15.5.2.1	Identification of Causes and Accident Description.....	15.5-5
15.5.2.2	Analysis of Effects and Consequences	15.5-7

TABLE OF CONTENTS (Cont.)

<u>Section</u>	<u>Title</u>	<u>Page</u>
	15.5.2.3 Results	15.5-8
	15.5.2.4 Conclusions	15.5-9
15.5.3	Boiling Water Reactor Transients	15.5-10
15.5.4	Combined License Information.....	15.5-10
15.5.5	References.....	15.5-10
15.6	Decrease in Reactor Coolant Inventory	15.6-1
15.6.1	Inadvertent Opening of a Pressurizer Safety Valve or Inadvertent Operation of the ADS	15.6-1
	15.6.1.1 Identification of Causes and Accident Description.....	15.6-1
	15.6.1.2 Analysis of Effects and Consequences	15.6-2
	15.6.1.3 Conclusion.....	15.6-4
15.6.2	Failure of Small Lines Carrying Primary Coolant Outside Containment.....	15.6-4
	15.6.2.1 Source Term	15.6-5
	15.6.2.2 Release Pathway	15.6-5
	15.6.2.3 Dose Calculation Models	15.6-5
	15.6.2.4 Analytical Assumptions and Parameters	15.6-5
	15.6.2.5 Identification of Conservatisms	15.6-5
	15.6.2.6 Doses	15.6-5
15.6.3	Steam Generator Tube Rupture.....	15.6-6
	15.6.3.1 Identification of Cause and Accident Description	15.6-6
	15.6.3.2 Analysis of Effects and Consequences	15.6-9
	15.6.3.3 Radiological Consequences.....	15.6-13
	15.6.3.4 Conclusions	15.6-15
15.6.4	Spectrum of Boiling Water Reactor Steam System Piping Failures Outside of Containment	15.6-16
15.6.5	Loss-of-coolant Accidents Resulting from a Spectrum of Postulated Piping Breaks Within the Reactor Coolant Pressure Boundary	15.6-16
	15.6.5.1 Identification of Causes and Frequency Classification	15.6-16
	15.6.5.2 Basis and Methodology for LOCA Analyses	15.6-17
	15.6.5.3 Radiological Consequences.....	15.6-19
	15.6.5.4 Core and System Performance.....	15.6-24
	15.6.5.4A Large-break LOCA Analysis Methodology and Results	15.6-24
	15.6.5.4B Small-break LOCA Analyses	15.6-31
	15.6.5.4C Post-LOCA Long-Term Cooling	15.6-47
15.6.6	References.....	15.6-54
15.7	Radioactive Release from a Subsystem or Component	15.7-1
15.7.1	Gas Waste Management System Leak or Failure	15.7-1
15.7.2	Liquid Waste Management System Leak or Failure (Atmospheric Release).....	15.7-1

TABLE OF CONTENTS (Cont.)

<u>Section</u>	<u>Title</u>	<u>Page</u>
15.7.3	Release of Radioactivity to the Environment Due to a Liquid Tank Failure	15.7-1
15.7.4	Fuel Handling Accident	15.7-1
15.7.4.1	Source Term	15.7-2
15.7.4.2	Release Pathways	15.7-3
15.7.4.3	Dose Calculation Models	15.7-3
15.7.4.4	Identification of Conservatisms	15.7-3
15.7.4.5	Offsite Doses	15.7-5
15.7.5	Spent Fuel Cask Drop Accident.....	15.7-5
15.7.6	Combined License Information.....	15.7-5
15.7.7	References.....	15.7-5
15.8	Anticipated Transients Without Scram.....	15.8-1
15.8.1	General Background	15.8-1
15.8.2	Anticipated Transients Without Scram in the AP1000	15.8-1
15.8.3	Conclusion	15.8-1
15.8.4	Combined License Information.....	15.8-1
15.8.5	References.....	15.8-1
APPENDIX 15A EVALUATION MODELS AND PARAMETERS FOR ANALYSIS OF RADIOPHYSICAL CONSEQUENCES OF ACCIDENTS		15A-1
15A.1	Offsite Dose Calculation Models	15A-1
15A.1.1	Immersion Dose (Effective Dose Equivalent).....	15A-1
15A.1.2	Inhalation Dose (Committed Effective Dose Equivalent)	15A-1
15A.1.3	Total Dose (Total Effective Dose Equivalent)	15A-2
15A.2	Main Control Room Dose Models.....	15A-2
15A.2.1	Immersion Dose Models	15A-2
15A.2.2	Inhalation Dose	15A-3
15A.2.3	Total Dose (Total Effective Dose Equivalent)	15A-3
15A.3	General Analysis Parameters.....	15A-3
15A.3.1	Source Terms	15A-3
15A.3.1.1	Primary Coolant Source Term	15A-3
15A.3.1.2	Secondary Coolant Source Term	15A-4
15A.3.1.3	Core Source Term	15A-4
15A.3.2	Nuclide Parameters	15A-4
15A.3.3	Atmospheric Dispersion Factors	15A-5
15A.4	References.....	15A-5
APPENDIX 15B REMOVAL OF AIRBORNE ACTIVITY FROM THE CONTAINMENT ATMOSPHERE FOLLOWING A LOCA		15B-1
15B.1	Elemental Iodine Removal	15B-1
15B.2	Aerosol Removal	15B-1

TABLE OF CONTENTS (Cont.)

<u>Section</u>	<u>Title</u>	<u>Page</u>
15B.2.1	Mathematical Models.....	15B-2
15B.2.1.1	Sedimentation.....	15B-2
15B.2.1.2	Diffusiophoresis	15B-4
15B.2.1.3	Thermophoresis	15B-5
15B.2.2	Other Removal Mechanisms	15B-6
15B.2.3	Validation of Removal Mechanisms	15B-6
15B.2.4	Parameters and Assumptions for Calculating Aerosol Removal Coefficients.....	15B-6
15B.2.4.1	Containment Geometry.....	15B-6
15B.2.4.2	Source Size Distribution.....	15B-6
15B.2.4.3	Aerosol Void Fraction	15B-7
15B.2.4.4	Fission Product Release Fractions	15B-7
15B.2.4.5	Inert Aerosol Species.....	15B-7
15B.2.4.6	Aerosol Release Timing and Rates.....	15B-7
15B.2.4.7	Containment Thermal-hydraulic Data	15B-8
15B.2.5	Aerosol Removal Coefficients	15B-8
15B.3	References	15B-8

LIST OF TABLES

<u>Table No.</u>	<u>Title</u>	<u>Page</u>
15.0-1	Nuclear Steam Supply System Power Ratings	15.0-16
15.0-2	Summary of Initial Conditions and Computer Codes Used (Sheets 1 – 5).....	15.0-17
15.0-3	Nominal Values of Pertinent Plant Parameters Used in Accident Analyses.....	15.0-22
15.0-4a	Protection and Safety Monitoring System Setpoints and Time Delay Assumed in Accident Analyses (Sheets 1 – 2)	15.0-23
15.0-4b	Limiting Delay Times for Equipment Assumed in Accident Analyses	15.0-25
15.0-5	Determination of Maximum Power Range Neutron Flux Channel Trip Setpoint, Based on Nominal Setpoint and Inherent Typical Instrumentation Uncertainties	15.0-26
15.0-6	Plant Systems And Equipment Available for Transient and Accident Conditions (Sheets 1 – 4)	15.0-27
15.0-7	Single Failures Assumed in Accident Analyses (Sheets 1 –2)	15.0-31
15.0-8	Nonsafety-Related System and Equipment Used for Mitigation of Accidents	15.0-33
15.1.2-1	Time Sequence of Events for Incidents that Result in an Increase in Heat Removal From the Primary System (Sheets 1 – 2).....	15.1-25
15.1.5-1	Parameters Used in Evaluating the Radiological Consequences of a Main Steam Line Break.....	15.1-27
15.2-1	Time Sequence of Events for Incidents Which Result in a Decrease in Heat Removal by the Secondary System (Sheets 1 – 7)	15.2-22
15.3-1	Time Sequence of Events for Incidents that Result in a Decrease in Reactor Coolant System Flow Rate	15.3-12
15.3-2	Summary of Results for Locked Rotor Transients (Four Reactor Coolant Pumps Operating Initially)	15.3-13
15.3-3	Parameters Used in Evaluating the Radiological Consequences of a Locked Rotor Accident (Sheets 1 – 2).....	15.3-14
15.4-1	Time Sequence of Events for Incidents Which Result in Reactivity and Power Distribution Anomalies (Sheets 1 – 3)	15.4-40
15.4-2	Parameters	15.4-43
15.4-3	Parameters Used in the Analysis of the Rod Cluster Control Assembly Ejection Accident	15.4-44
15.4-4	Parameters Used in Evaluating the Radiological Consequences of a Rod Ejection Accident (Sheets 1 – 2)	15.4-45
15.5-1	Time Sequence of Events for Incidents Which Result in an Increase in Reactor Coolant Inventory (Sheets 1 – 2).....	15.5-11
15.6.1-1	Time Sequence of Events for Incidents that Cause a Decrease in Reactor Coolant Inventory.....	15.6-57
15.6.2-1	Parameters Used in Evaluating the Radiological Consequences of a Small Line Break Outside Containment	15.6-58
15.6.3-1	Steam Generator Tube Rupture Sequence of Events.....	15.6-59
15.6.3-2	Steam Generator Tube Rupture Mass Release Results.....	15.6-60
15.6.3-3	Parameters Used in Evaluating the Radiological Consequences of a Steam Generator Tube Rupture	15.6-61

LIST OF TABLES (Cont.)

Table No.	Title	Page
15.6.5-1	Core Activity Releases to the Containment Atmosphere.....	15.6-62
15.6.5-2	Assumptions and Parameters Used in Calculating Radiological Consequences of a Loss-Of-Coolant Accident (Sheets 1 – 3)	15.6-63
15.6.5-3	Radiological Consequences of a Loss-of-Coolant Accident with Core Melt.....	15.6-66
15.6.5-4	Major Plant Parameter Assumptions Used in the Best-Estimate Large-Break LOCA Analysis	15.6-67
15.6.5-5	AP1000 LOCA Chronology.....	15.6-68
15.6.5-6	Reference Transient DECLG Break Sequence of Events.....	15.6-69
15.6.5-7	DECL Split Break Results.....	15.6-70
15.6.5-8	Best-Estimate Large-Break LOCA Results	15.6-71
15.6.5-9	Initial Conditions for AP1000 Small-Break LOCA Analysis.....	15.6-72
15.6.5-10	AP1000 ADS Parameters	15.6-73
15.6.5-11	Inadvertent ADS Depressurization Sequence of Events.....	15.6-74
15.6.5-12	2-Inch Cold Leg Break in CLBL Line Sequence of Events	15.6-75
15.6.5-13	Double-Ended Injection Line Break Sequence of Events – 20 psi	15.6-76
15.6.5-13A	Double-Ended Injection Line Break Sequence of Events – 14.7 psi	15.6-77
15.6.5-14	10-Inch Cold Leg Break in Sequence of Events.....	15.6-78
15.6.5-15	Double-Ended Injection Line Break Sequence of Events (Entrainment Sensitivity)	15.6-79
15.7-1	Assumptions Used to Determine Fuel Handling Accident Radiological Consequences.....	15.7-6
15A-1	Reactor Coolant Iodine Concentrations for Maximum Iodine Spike of 60 µCi/g Dose Equivalent I-131.....	15A-7
15A-2	Iodine Appearance Rates in the Reactor Coolant	15A-7
15A-3	Reactor Core Source Term (Sheets 1 – 2)	15A-8
15A-4	Nuclide Parameters (Sheets 1 – 4).....	15A-10
15A-5	Offsite Atmospheric Dispersion Factors (χ/Q) for Accident Dose Analysis.....	15A-14
15A-6	Control Room Atmospheric Dispersion Factors (χ/Q) for Accident Dose Analysis.....	15A-15
15A-7	Control Room Source/Receptor Data for Determination of Atmospheric Dispersion Factors	15A-17
15B-1	Aerosol Removal Coefficients in the AP1000 Containment Following a Design Basis LOCA With Core Melt (Sheets 1 – 3)	15B-10

LIST OF FIGURES

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
15.0.3-1	Overpower and Overtemperature ΔT Protection	15.0-34
15.0.3-2	AP1000 Loop Layout.....	15.0-35
15.0.4-1	Doppler Power Coefficient used in Accident Analysis	15.0-36
15.0.5-1	RCCA Position Versus Time to Dashpot	15.0-37
15.0.5-2	Normalized Rod Worth Versus Position	15.0-38
15.0.5-3	Normalized RCCA Bank Reactivity Worth Versus Drop Time	15.0-39
15.1.2-1	Feedwater Control Valve Malfunction Nuclear Power.....	15.1-28
15.1.2-2	Feedwater Control Valve Malfunction Loop ΔT	15.1-29
15.1.2-3	Feedwater Control Valve Malfunction Core Coolant Mass Flow.....	15.1-30
15.1.3-1	Nuclear Power (Fraction of Nominal) Versus Time for 10-percent Step Load Increase, Manual Control and Minimum Moderator Feedback.....	15.1-31
15.1.3-2	Pressurizer Pressure (psia) Versus Time for 10-percent Step Load Increase, Manual Control and Minimum Moderator Feedback.....	15.1-32
15.1.3-3	Pressurizer Water Volume (ft^3) Versus Time for 10-percent Step Load Increase, Manual Control and Minimum Moderator Feedback	15.1-33
15.1.3-4	Core Average Temperature ($^{\circ}\text{F}$) Versus Time for 10-percent Step Load Increase, Manual Control and Minimum Moderator Feedback	15.1-34
15.1.3-5	DNBR Versus Time for 10-percent Step Load Increase, Manual Control and Minimum Moderator Feedback	15.1-35
15.1.3-6	Nuclear Power (Fraction of Nominal) Versus Time for 10-percent Step Load Increase, Manual Control and Maximum Moderator Feedback	15.1-36
15.1.3-7	Pressurizer Pressure (psia) Versus Time for 10-percent Step Load Increase, Manual Control and Maximum Moderator Feedback	15.1-37
15.1.3-8	Pressurizer Water Volume (ft^3) Versus Time for 10-percent Step Load Increase, Manual Control and Maximum Moderator Feedback	15.1-38
15.1.3-9	Core Average Temperature ($^{\circ}\text{F}$) Versus Time for 10-percent Step Load Increase, Manual Control and Maximum Moderator Feedback	15.1-39
15.1.3-10	DNBR Versus Time for 10-percent Step Load Increase, Manual Control and Maximum Moderator Feedback.....	15.1-40
15.1.3-11	Nuclear Power (Fraction of Nominal) Versus Time for 10-percent Step Load Increase, Automatic Control and Minimum Moderator Feedback	15.1-41
15.1.3-12	Pressurizer Pressure (psia) Versus Time for 10-percent Step Load Increase, Automatic Control and Minimum Moderator Feedback	15.1-42
15.1.3-13	Pressurizer Water Volume (ft^3) Versus Time for 10-percent Step Load Increase, Automatic Control and Minimum Moderator Feedback	15.1-43
15.1.3-14	Core Average Temperature ($^{\circ}\text{F}$) Versus Time for 10-percent Step Load Increase, Automatic Control and Minimum Moderator Feedback	15.1-44
15.1.3-15	DNBR Versus Time for 10-percent Step Load Increase, Automatic Control and Minimum Moderator Feedback	15.1-45
15.1.3-16	Nuclear Power (Fraction of Nominal) Versus Time for 10-percent Step Load Increase, Automatic Control and Maximum Moderator Feedback.....	15.1-46

LIST OF FIGURES (Cont.)

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
15.1.3-17	Pressurizer Pressure (psia) Versus Time for 10-percent Step Load Increase, Automatic Control and Maximum Moderator Feedback.....	15.1-47
15.1.3-18	Pressurizer Water Volume (ft ³) Versus Time for 10-percent Step Load Increase, Automatic Control and Maximum Moderator Feedback.....	15.1-48
15.1.3-19	Core Average Temperature (°F) Versus Time for 10-percent Step Load Increase, Automatic Control and Maximum Moderator Feedback.....	15.1-49
15.1.3-20	DNBR Versus Time for 10-percent Step Load Increase, Automatic Control and Maximum Moderator Feedback	15.1-50
15.1.4-1	K _{eff} Versus Core Inlet Temperature Steam Line Break Events.....	15.1-51
15.1.4-2	Nuclear Power Transient Inadvertent Opening of a Steam Generator Relief or Safety Valve	15.1-52
15.1.4-3	Core Heat Flux Transient Inadvertent Opening of a Steam Generator Relief or Safety Valve	15.1-53
15.1.4-4	Loop 1 Reactor Coolant Temperatures Inadvertent Opening of a Steam Generator Relief or Safety Valve.....	15.1-54
15.1.4-5	Loop 2 (Faulted Loop) Reactor Coolant Temperatures Inadvertent Opening of a Steam Generator Relief or Safety Valve.....	15.1-55
15.1.4-6	Reactor Coolant System Pressure Transient Inadvertent Opening of a Steam Generator Relief or Safety Valve.....	15.1-56
15.1.4-7	Pressurizer Water Volume Transient Inadvertent Opening of a Steam Generator Relief or Safety Valve.....	15.1-57
15.1.4-8	Core Flow Transient Inadvertent Opening of a Steam Generator Relief or Safety Valve.....	15.1-58
15.1.4-9	Feedwater Flow Transient Inadvertent Opening of a Steam Generator Relief or Safety Valve	15.1-59
15.1.4-10	Core Boron Transient Inadvertent Opening of a Steam Generator Relief or Safety Valve	15.1-60
15.1.4-11	Steam Pressure Transient Inadvertent Opening of a Steam Generator Relief or Safety Valve	15.1-61
15.1.4-12	Steam Flow Transient Inadvertent Opening of a Steam Generator Relief or Safety Valve	15.1-62
15.1.5-1	Nuclear Power Transient Steam System Piping Feature.....	15.1-63
15.1.5-2	Core Heat Flux Transient Steam System Piping Failure	15.1-64
15.1.5-3	Loop 1 Reactor Coolant Temperatures Steam System Piping Failure	15.1-65
15.1.5-4	Loop 2 Reactor Coolant Temperatures Steam System Piping Failure	15.1-66
15.1.5-5	Reactor Coolant System Pressure Transient Steam System Piping Failure	15.1-67
15.1.5-6	Pressurizer Water Volume Transient Steam System Piping Failure	15.1-68
15.1.5-7	Core Flow Transient Steam System Piping Failure	15.1-69
15.1.5-8	Feedwater Flow Transient Steam System Piping Failure	15.1-70
15.1.5-9	Core Boron Transient Steam System Piping Failure	15.1-71
15.1.5-10	Steam Pressure Transient Steam System Piping Failure.....	15.1-72
15.1.5-11	Steam Flow Transient Steam System Piping Failure.....	15.1-73

LIST OF FIGURES (Cont.)

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
15.1.5-12	Core Makeup Tank Injection Flow Steam System Piping Failure.....	15.1-74
15.1.5-13	Core Makeup Tank Water Volume Steam System Piping Failure.....	15.1-75
15.1.6-1	Nuclear Power Transient Inadvertent Operation of the PRHR	15.1-76
15.1.6-2	Core Heat Flux Transient Inadvertent Operation of the PRHR	15.1-77
15.1.6-3	Reactor Vessel Inlet Temperature Transient Inadvertent Operation of the PRHR	15.1-78
15.1.6-4	Reactor Coolant System Pressure Transient Inadvertent Operation of the PRHR	15.1-79
15.1.6-5	Reactor Coolant System Flow Transient Inadvertent Operation of the PRHR	15.1-80
15.1.6-6	DNBR Transient Inadvertent Operation of the PRHR	15.1-81
15.1.6-7	PRHR Flow Transient Inadvertent Operation of the PRHR	15.1-82
15.1.6-8	PRHR Heat Transfer Transient Inadvertent Operation of the PRHR	15.1-83
15.2.3-1	Nuclear Power (Fraction of Nominal) versus Time for Turbine Trip Accident with Pressurizer Spray and Minimum Moderator Feedback	15.2-29
15.2.3-2	Pressurizer Pressure (psia) versus Time for Turbine Trip Accident with Pressurizer Spray and Minimum Moderator Feedback.....	15.2-30
15.2.3-3	Pressurizer Water Volume (ft^3) versus Time for Turbine Trip Accident with Pressurizer Spray and Minimum Moderator Feedback.....	15.2-31
15.2.3-4	Vessel Inlet Temperature ($^{\circ}\text{F}$) versus Time for Turbine Trip Accident with Pressurizer Spray and Minimum Moderator Feedback.....	15.2-32
15.2.3-5	Vessel Average Temperature ($^{\circ}\text{F}$) versus Time for Turbine Trip Accident with Pressurizer Spray and Minimum Moderator Feedback.....	15.2-33
15.2.3-6	DNBR versus Time for Turbine Trip Accident with Pressurizer Spray and Minimum Moderator Feedback	15.2-34
15.2.3-7	Core Mass Flow Rate (Fraction of Initial) versus Time for Turbine Trip Accident with Pressurizer Spray and Minimum Moderator Feedback	15.2-35
15.2.3-8	Nuclear Power (Fraction of Nominal) versus Time for Turbine Trip Accident with Pressurizer Spray and Maximum Moderator Feedback.....	15.2-36
15.2.3-9	Pressurizer Pressure (psia) versus Time for Turbine Trip Accident with Pressurizer Spray and Maximum Moderator Feedback	15.2-37
15.2.3-10	Pressurizer Water Volume (ft^3) versus Time for Turbine Trip Accident with Pressurizer Spray and Maximum Moderator Feedback	15.2-38
15.2.3-11	Vessel Inlet Temperature ($^{\circ}\text{F}$) versus Time for Turbine Trip Accident with Pressurizer Spray and Maximum Moderator Feedback	15.2-39
15.2.3-12	Vessel Average Temperature ($^{\circ}\text{F}$) versus Time for Turbine Trip Accident with Pressurizer Spray and Maximum Moderator Feedback	15.2-40
15.2.3-13	DNBR versus Time for Turbine Trip Accident with Pressurizer Spray and Maximum Moderator Feedback.....	15.2-41
15.2.3-14	Core Mass Flow Rate (Fraction of Initial) versus Time for Turbine Trip Accident with Pressurizer Spray and Maximum Moderator Feedback.....	15.2-42

LIST OF FIGURES (Cont.)

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
15.2.3-15	Nuclear Power (Fraction of Nominal) versus Time for Turbine Trip Accident Without Pressurizer Spray and Minimum Moderator Feedback	15.2-43
15.2.3-16	Pressurizer Pressure (psia) versus Time for Turbine Trip Accident Without Pressurizer Spray and Minimum Moderator Feedback.....	15.2-44
15.2.3-17	Pressurizer Water Volume (ft^3) versus Time for Turbine Trip Accident Without Pressurizer Spray and Minimum Moderator Feedback.....	15.2-45
15.2.3-18	Vessel Inlet Temperature ($^{\circ}\text{F}$) versus Time for Turbine Trip Accident Without Pressurizer Spray and Minimum Moderator Feedback.....	15.2-46
15.2.3-19	Vessel Average Temperature ($^{\circ}\text{F}$) versus Time for Turbine Trip Accident Without Pressurizer Spray and Minimum Moderator Feedback.....	15.2-47
15.2.3-20	Core Mass Flow Rate (Fraction of Initial) versus Time for Turbine Trip Accident Without Pressurizer Spray and Minimum Moderator Feedback	15.2-48
15.2.3-21	Nuclear Power (Fraction of Nominal) versus Time for Turbine Trip Accident Without Pressurizer Spray and Maximum Moderator Feedback.....	15.2-49
15.2.3-22	Pressurizer Pressure (psia) versus Time for Turbine Trip Accident Without Pressurizer Spray and Maximum Moderator Feedback.....	15.2-50
15.2.3-23	Pressurizer Water Volume (ft^3) versus Time for Turbine Trip Accident Without Pressurizer Spray and Maximum Moderator Feedback.....	15.2-51
15.2.3-24	Vessel Inlet Temperature ($^{\circ}\text{F}$) versus Time for Turbine Trip Accident Without Pressurizer Spray and Maximum Moderator Feedback	15.2-52
15.2.3-25	Vessel Average Temperature ($^{\circ}\text{F}$) versus Time for Turbine Trip Accident Without Pressurizer Spray and Maximum Moderator Feedback.....	15.2-53
15.2.3-26	Core Mass Flow Rate (Fraction of Initial) versus Time for Turbine Trip Accident Without Pressurizer Spray and Maximum Moderator Feedback.....	15.2-54
15.2.6-1	Nuclear Power Transient for Loss of ac Power to the Plant Auxiliaries.....	15.2-55
15.2.6-2	Core Heat Flux Transient for Loss of ac Power to the Plant Auxiliaries	15.2-56
15.2.6-3	Pressurizer Pressure Transient for Loss of ac Power to the Plant Auxiliaries	15.2-57
15.2.6-4	Pressurizer Water Volume Transient for Loss of ac Power to the Plant Auxiliaries.....	15.2-58
15.2.6-5	Reactor Coolant System Temperature Transients in Loop Containing the PRHR for Loss of ac Power to the Plant Auxiliaries	15.2-59
15.2.6-6	Reactor Coolant System Temperature Transients in Loop Not Containing the PRHR for Loss of ac Power to the Plant Auxiliaries	15.2-60
15.2.6-7	Steam Generator Pressure Transient for Loss of ac Power to the Plant Auxiliaries.....	15.2-61
15.2.6-8	PRHR Flow Rate Transient for Loss of ac Power to the Plant Auxiliaries.....	15.2-62
15.2.6-9	PRHR Heat Flux Transient for Loss of ac Power to the Plant Auxiliaries	15.2-63
15.2.6-10	Reactor Coolant Volumetric Flow Rate Transient for Loss of ac Power to the Plant Auxiliaries	15.2-64
15.2.6-11	Steam Generator Inventory Transient for Loss of ac Power to the Plant Auxiliaries.....	15.2-65
15.2.6-12	DNB Ratio Transient for Loss of ac Power to the Plant Auxiliaries	15.2-66

LIST OF FIGURES (Cont.)

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
15.2.7-1	Nuclear Power Transient for Loss of Normal Feedwater Flow	15.2-67
15.2.7-2	Reactor Coolant System Volumetric Flow Transient for Loss of Normal Feedwater Flow.....	15.2-68
15.2.7-3	Reactor Coolant System Temperature Transients in Loop Containing the PRHR for Loss Normal Feedwater Flow.....	15.2-69
15.2.7-4	Reactor Coolant System Temperature Transients in Loop Not Containing the PRHR for Loss of Normal Feedwater Flow.....	15.2-70
15.2.7-5	Pressurizer Pressure Transient for Loss of Normal Feedwater Flow	15.2-71
15.2.7-6	Pressurizer Water Volume Transient for Loss of Normal Feedwater Flow	15.2-72
15.2.7-7	Steam Generator Pressure Transient for Loss of Normal Feedwater Flow.....	15.2-73
15.2.7-8	Steam Generator Inventory Transient for Loss of Normal Feedwater Flow	15.2-74
15.2.7-9	PRHR Heat Flux Transient for Loss of Normal Feedwater Flow.....	15.2-75
15.2.7-10	CMT Injection Flow Rate Transient for Loss of Normal Feedwater Flow.....	15.2-76
15.2.8-1	Nuclear Power Transient for Main Feedwater Line Rupture.....	15.2-77
15.2.8-2	Core Heat Flux Transient for Main Feedwater Line Rupture.....	15.2-78
15.2.8-3	Faulted Loop Reactor Coolant System Temperature Transients for Main Feedwater Line Rupture.....	15.2-79
15.2.8-4	Intact Loop Reactor Coolant System Temperature Transients for Main Feedwater Line Rupture.....	15.2-80
15.2.8-5	Pressurizer Pressure Transient for Main Feedwater Line Rupture	15.2-81
15.2.8-6	Pressurizer Water Volume Transient for Main Feedwater Line Rupture	15.2-82
15.2.8-7	Steam Generator Pressure Transient for Main Feedwater Line Rupture	15.2-83
15.2.8-8	PRHR Flow Rate Transient for Main Feedwater Line Rupture.....	15.2-84
15.2.8-9	PRHR Heat Flux Transient for Main Feedwater Line Rupture	15.2-85
15.2.8-10	CMT Injection Flow Rate Transient for Main Feedwater Line Rupture	15.2-86
15.3.1-1	Core Mass Flow Transient for Four Cold Legs in Operation, Two Pumps Coasting Down.....	15.3-16
15.3.1-2	Nuclear Power Transient for Four Cold Legs in Operation, Two Pumps Coasting Down.....	15.3-17
15.3.1-3	Pressurizer Pressure Transient for Four Cold Legs in Operation, Two Pumps Coasting Down.....	15.3-18
15.3.1-4	Average Channel Heat Flux Transient for Four Cold Legs in Operation, Two Pumps Coasting Down	15.3-19
15.3.1-5	Hot Channel Heat Flux Transient for Four Cold Legs in Operation, Two Pumps Coasting Down.....	15.3-20
15.3.1-6	DNB Transient for Four Cold Legs in Operation, Two Pumps Coasting Down.....	15.3-21
15.3.2-1	Flow Transient for Four Cold Legs in Operation, Four Pumps Coasting Down.....	15.3-22
15.3.2-2	Nuclear Power Transient for Four Cold Legs in Operation, Four Pumps Coasting Down.....	15.3-23
15.3.2-3	Pressurizer Pressure Transient for Four Cold Legs in Operation, Four Pumps Coasting Down.....	15.3-24

LIST OF FIGURES (Cont.)

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
15.3.2-4	Average Channel Heat Flux Transient for Four Cold Legs in Operation, Four Pumps Coasting Down.....	15.3-25
15.3.2-5	Hot Channel Heat Flux Transient for Four Cold Legs in Operation, Four Pumps Coasting Down.....	15.3-26
15.3.2-6	DNBR Transient for Four Cold Legs in Operation, Four Pumps Coasting Down.....	15.3-27
15.3.3-1	Core Mass Flow Transient for Four Cold Legs in Operation, One Locked Rotor	15.3-28
15.3.3-2	Faulted Loop Volumetric Flow Transient for Four Cold Legs in Operation, One Locked Rotor	15.3-29
15.3.3-3	Peak Reactor Coolant Pressure for Four Cold Legs in Operation, One Locked Rotor	15.3-30
15.3.3-4	Average Channel Heat Flux Transient for Four Cold Legs in Operation, One Locked Rotor	15.3-31
15.3.3-5	Hot Channel Heat Flux Transient for Four Cold Legs in Operation, One Locked Rotor	15.3-32
15.3.3-6	Nuclear Power Transient for Four Cold Legs in Operation, One Locked Rotor	15.3-33
15.3.3-7	Cladding Inside Temperature Transient for Four Cold Legs in Operation, One Locked Rotor	15.3-34
15.4.1-1	RCCA Withdrawal from Subcritical Nuclear Power.....	15.4-47
15.4.1-2	RCCA Withdrawal from Subcritical Average Channel Core Heat Flux	15.4-48
15.4.1-3	RCCA Withdrawal from Subcritical Hot Spot Fuel Average Temperature (Sheet 1 of 2).....	15.4-49
15.4.1-3	RCCA Withdrawal from Subcritical Hot Spot Cladding Inner Temperature (Sheet 2 of 2).....	15.4-50
15.4.2-1	Nuclear Power Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (75 pcm/s).....	15.4-51
15.4.2-2	Thermal Flux Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (75 pcm/s).....	15.4-52
15.4.2-3	Pressurizer Pressure Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (75 pcm/s).....	15.4-53
15.4.2-4	Pressurizer Water Volume Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (75 pcm/s)	15.4-54
15.4.2-5	Core Coolant Average Temperature Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (75 pcm/s)	15.4-55
15.4.2-6	DNBR Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (75 pcm/s)	15.4-56
15.4.2-7	Core Mass Flow Rate Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (75 pcm/s)	15.4-57

LIST OF FIGURES (Cont.)

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
15.4.2-8	Nuclear Power Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (3 pcm/s).....	15.4-58
15.4.2-9	Thermal Flux Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (3 pcm/s).....	15.4-59
15.4.2-10	Pressurizer Pressure Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (3 pcm/s).....	15.4-60
15.4.2-11	Pressurizer Water Volume Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (3 pcm/s)	15.4-61
15.4.2-12	Core Coolant Average Temperature Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (3 pcm/s)	15.4-62
15.4.2-13	DNBR Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (3 pcm/s)	15.4-63
15.4.2-14	Core Mass Flow Rate Transient for an Uncontrolled RCCA Bank Withdrawal from Full Power With Maximum Reactivity Feedback (3 pcm/s)	15.4-64
15.4.2-15	Minimum DNBR Versus Reactivity Insertion Rate for Rod Withdrawal at 100-percent Power.....	15.4-65
15.4.2-16	Minimum DNBR Versus Reactivity Insertion Rate for Rod Withdrawal at 60-percent Power.....	15.4-66
15.4.2-17	Minimum DNBR Versus Reactivity Insertion Rate for Rod Withdrawal at 10-percent Power.....	15.4-67
15.4.3-1	Nuclear Power Transient for Dropped RCCA	15.4-68
15.4.3-2	Core Heat Flux Transient for Dropped RCCA	15.4-69
15.4.3-3	Reactor Coolant System Pressure Transient for Dropped RCCA	15.4-70
15.4.3-4	RCS Average Temperature Transient for Dropped RCCA	15.4-71
15.4.7-1	Representative Percent Change in Local Assembly Average Power for Interchange Between Region 1 and Region 3 Assembly	15.4-72
15.4.7-2	Representative Percent Change in Local Assembly Average Power for Interchange Between Region 1 and Region 2 Assembly with the BP Rods Transferred to Region 1 Assembly	15.4-73
15.4.7-3	Representative Percent Change in Local Assembly Average Power for Enrichment Error (Region 2 Assembly Loaded into Core Central Position)	15.4-74
15.4.7-4	Representative Percent Change in Local Assembly Average Power for Loading Region 2 Assembly into Region 1 Position Near Core Periphery	15.4-75
15.4.8-1	Nuclear Power Transient Versus Time at Beginning of Life, Full Power	15.4-76
15.4.8-2	Hot Spot Fuel, Average Fuel, and Outer Cladding Temperature Versus Time at Beginning of Life, Full Power.....	15.4-77
15.4.8-3	Nuclear Power Transient Versus Time at End of Life, Zero Power	15.4-78
15.4.8-4	Hot Spot Fuel, Average Fuel, and Outer Cladding Temperature Versus Time at End of Life, Zero Power.....	15.4-79
15.5.1-1	Core Nuclear Power Transient for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves.....	15.5-13

LIST OF FIGURES (Cont.)

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
15.5.1-2	RCS Temperature Transient in Loop Containing the PRHR for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves.....	15.5-14
15.5.1-3	RCS Temperature Transient in Loop Not Containing the PRHR for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves.....	15.5-15
15.5.1-4	Pressurizer Pressure Transient for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves.....	15.5-16
15.5.1-5	Pressurizer Water Volume Transient for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves.....	15.5-17
15.5.1-6	DNBR Transient for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves	15.5-18
15.5.1-7	Steam Generator Pressure Transient for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves.....	15.5-19
15.5.1-8	Inadvertent Actuated CMT Flow Rate Transient for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves	15.5-20
15.5.1-9	Intact CMT Flow Rate Transient for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves	15.5-21
15.5.1-10	PRHR and Core Heat Flux Transient for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves	15.5-22
15.5.1-11	PRHR Flow Rate Transient for Inadvertent Operation of the Emergency Core Cooling System Due to a Spurious Opening of the Core Makeup Tank Discharge Valves	15.5-23
15.5.2-1	Core Nuclear Power Transient for Chemical and Volume Control System Malfunction	15.5-24
15.5.2-2	RCS Temperature Transient in Loop Containing the PRHR for Chemical and Volume Control System Malfunction	15.5-25
15.5.2-3	RCS Temperature Transient in Loop Not Containing the PRHR for Chemical and Volume Control System Malfunction	15.5-26
15.5.2-4	Pressurizer Pressure Transient for Chemical and Volume Control System Malfunction	15.5-27
15.5.2-5	Pressurizer Water Volume Transient for Chemical and Volume Control System Malfunction	15.5-28
15.5.2-6	DNBR Transient for Chemical and Volume Control System Malfunction	15.5-29
15.5.2-7	CVS Flow Rate Transient for Chemical and Volume Control System Malfunction	15.5-30

LIST OF FIGURES (Cont.)

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
15.5.2-8	Steam Generator Pressure Transient for Chemical and Volume Control System Malfunction	15.5-31
15.5.2-9	CMT Injection Line and Balance Line Flow Transient for Chemical and Volume Control System Malfunction.....	15.5-32
15.5.2-10	PRHR and Core Heat Flux Transient for Chemical and Volume Control System Malfunction	15.5-33
15.5.2-11	PRHR Flow Rate Transient for Chemical and Volume Control System Malfunction.....	15.5-34
15.6.1-1	Nuclear Power Transient Inadvertent Opening of a Pressurizer Safety Valve.....	15.6-80
15.6.1-2	DNBR Transient Inadvertent Opening of a Pressurizer Safety Valve	15.6-81
15.6.1-3	Pressurizer Pressure Transient Inadvertent Opening of a Pressurizer Safety Valve ..	15.6-82
15.6.1-4	Vessel Average Temperature Inadvertent Opening of a Pressurizer Safety Valve	15.6-83
15.6.1-5	Core Mass Flow Rate Inadvertent Opening of a Pressurizer Safety Valve.....	15.6-84
15.6.1-6	Nuclear Power Transient Inadvertent Opening of Two ADS Stage 1 Trains	15.6-85
15.6.1-7	DNBR Transient Inadvertent Opening of Two ADS Stage 1 Trains.....	15.6-86
15.6.1-8	Nuclear Power Transient Inadvertent Opening of Two ADS Stage 1 Trains	15.6-87
15.6.1-9	Nuclear Power Transient Inadvertent Opening of Two ADS Stage 1 Trains	15.6-88
15.6.1-10	Core Mass Flow Rate Inadvertent Opening of Two ADS Stage 1 Trains	15.6-89
15.6.3-1	Pressurizer Level for SGTR	15.6-90
15.6.3-2	Reactor Coolant System Pressure for SGTR	15.6-91
15.6.3-3	Secondary Pressure for SGTR.....	15.6-92
15.6.3-4	Intact Loop Hot and Cold Leg Reactor Coolant System Temperature for SGTR.....	15.6-93
15.6.3-5	Primary-to-Secondary Break Flow Rate for SGTR	15.6-94
15.6.3-6	Faulted Steam Generator Water Volume for SGTR	15.6-95
15.6.3-7	Faulted Steam Generator Mass Release Rate to the Atmosphere for SGTR	15.6-96
15.6.3-8	Intact Steam Generator Mass Release Rate to the Atmosphere for SGTR	15.6-97
15.6.3-9	Faulted Loop Chemical and Volume Control System and Core Makeup Tank Injection Flow for SGTR	15.6-98
15.6.3-10	Integrated Flashed Break Flow for SGTR	15.6-99
15.6.5.4A-1	PCT Among All Elevations for Each Fuel Rod.....	15.6-100
15.6.5.4A-2	Hot Rod Cladding Temperature Transient, PCT Elevation	15.6-101
15.6.5.4A-3	Hot Assembly Exit Vapor, Entrained Drop, Liquid Flow Rates	15.6-102
15.6.5.4A-4	Core Pressure	15.6-103
15.6.5.4A-5	Accumulator Flow Rate.....	15.6-104
15.6.5.4A-6	Intact Loop Core Makeup Tank Flow Rate	15.6-105
15.6.5.4A-7	Peripheral Assemblies Exit Vapor, Entrained Drop, Liquid Flow Rates.....	15.6-106
15.6.5.4A-8	Guide Tube Assemblies Exit Vapor, Entrained Drop, Liquid Flow Rates	15.6-107
15.6.5.4A-9	Open Hole Assemblies Exit Vapor, Entrained Drop, Liquid Flow Rates.....	15.6-108
15.6.5.4A-10	Steam Generator Side DECLG Break Flow Rate	15.6-109
15.6.5.4A-11	Vessel Side DECLG Break Flow Rate	15.6-110
15.6.5.4A-12	Core and Downcomer Collapsed Liquid Levels.....	15.6-111
15.6.5.4B-1	Inadvertent ADS – RCS Pressure.....	15.6-112
15.6.5.4B-2	Inadvertent ADS – Pressurizer Mixture Level	15.6-113
15.6.5.4B-3	Inadvertent ADS – ADS 1-3 Liquid Discharge.....	15.6-114

LIST OF FIGURES (Cont.)

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
15.6.5.4B-4	Inadvertent ADS – ADS 1-3 Vapor Discharge.....	15.6-115
15.6.5.4B-5	Inadvertent ADS – CMT-1 Injection Rate	15.6-116
15.6.5.4B-6	Inadvertent ADS – CMT-2 Injection Rate	15.6-117
15.6.5.4B-7	Inadvertent ADS – CMT-1 Mixture Level	15.6-118
15.6.5.4B-8	Inadvertent ADS – CMT-2 Mixture Level	15.6-119
15.6.5.4B-9	Inadvertent ADS – Downcomer Mixture Level	15.6-120
15.6.5.4B-10	Inadvertent ADS – Accumulator-1 Injection Rate.....	15.6-121
15.6.5.4B-11	Inadvertent ADS – Accumulator-2 Injection Rate.....	15.6-122
15.6.5.4B-12	Inadvertent ADS – ADS-4 Integrated Discharge	15.6-123
15.6.5.4B-13	Inadvertent ADS – IRWST-1 Injection Rate.....	15.6-124
15.6.5.4B-14	Inadvertent ADS – IRWST-2 Injection Rate.....	15.6-125
15.6.5.4B-15	Inadvertent ADS – RCS System Inventory	15.6-126
15.6.5.4B-16	Inadvertent ADS – Core/Upper Plenum Mixture Level	15.6-127
15.6.5.4B-17	2-Inch Cold Leg Break – RCS Pressure	15.6-128
15.6.5.4B-18	2-Inch Cold Leg Break – Pressurizer Mixture Level.....	15.6-129
15.6.5.4B-19	2-Inch Cold Leg Break – CMT-1 Mixture Level	15.6-130
15.6.5.4B-20	2-Inch Cold Leg Break – CMT-2 Mixture Level	15.6-131
15.6.5.4B-21	2-Inch Cold Leg Break – Downcomer Mixture Level.....	15.6-132
15.6.5.4B-22	2-Inch Cold Leg Break – CMT-1 Injection Rate	15.6-133
15.6.5.4B-23	2-Inch Cold Leg Break – CMT-2 Injection Rate	15.6-134
15.6.5.4B-24	2-Inch Cold Leg Break – Accumulator-1 Injection Rate.....	15.6-135
15.6.5.4B-25	2-Inch Cold Leg Break – Accumulator-2 Injection Rate.....	15.6-136
15.6.5.4B-26	2-Inch Cold Leg Break – IRWST-1 Injection Rate	15.6-137
15.6.5.4B-27	2-Inch Cold Leg Break – IRWST-2 Injection Rate	15.6-138
15.6.5.4B-28	2-Inch Cold Leg Break – ADS-4 Liquid Discharge	15.6-139
15.6.5.4B-29	2-Inch Cold Leg Break – RCS System Inventory.....	15.6-140
15.6.5.4B-30	2-Inch Cold Leg Break – Core/Upper Plenum Mixture Level.....	15.6-141
15.6.5.4B-31	2-Inch Cold Leg Break – ADS-4 Integrated Discharge	15.6-142
15.6.5.4B-32	2-Inch Cold Leg Break – Liquid Break Discharge	15.6-143
15.6.5.4B-33	2-Inch Cold Leg Break – Vapor Break Discharge.....	15.6-144
15.6.5.4B-34	2-Inch Cold Leg Break – PRHR Heat Removal Rate.....	15.6-145
15.6.5.4B-35	2-Inch Cold Leg Break – Integrated PRHR Heat Removal	15.6-146
15.6.5.4B-36	DEDVI – Vessel Side Liquid Break Discharge – 20 psi	15.6-147
15.6.5.4B-37	DEDVI – Vessel Side Vapor Break Discharge – 20 psi	15.6-148
15.6.5.4B-38	DEDVI – RCS Pressure – 20 psi.....	15.6-149
15.6.5.4B-39	DEDVI – Broken CMT Injection Rate – 20 psi	15.6-150
15.6.5.4B-40	DEDVI – Intact CMT Injection Rate – 20 psi	15.6-151
15.6.5.4B-41	DEDVI – Core/Upper Plenum Mixture Level – 20 psi	15.6-152
15.6.5.4B-42	DEDVI – Downcomer Mixture Level – 20 psi	15.6-153
15.6.5.4B-43	DEDVI – ADS 1-3 Vapor Discharge – 20 psi	15.6-154
15.6.5.4B-44	DEDVI – Core Exit Void Fraction – 20 psi	15.6-155
15.6.5.4B-45	DEDVI – Core Exit Liquid Flow Rate – 20 psi	15.6-156
15.6.5.4B-46	DEDVI – Core Exit Vapor Flow Rate – 20 psi	15.6-157

LIST OF FIGURES (Cont.)

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
15.6.5.4B-47	DEDVI – Lower Plenum to Core Flow Rate – 20 psi	15.6-158
15.6.5.4B-48	DEDVI – ADS-4 Liquid Discharge – 20 psi.....	15.6-159
15.6.5.4B-49	DEDVI – ADS-4 Integrated Discharge – 20 psi	15.6-160
15.6.5.4B-50	DEDVI – Intact Accumulator Flow Rate – 20 psi.....	15.6-161
15.6.5.4B-51	DEDVI – Intact IRWST Injection Rate – 20 psi	15.6-162
15.6.5.4B-52	DEDVI – Intact CMT Mixture Level – 20 psi	15.6-163
15.6.5.4B-53	DEDVI – RCS System Inventory – 20 psi	15.6-164
15.6.5.4B-54	DEDVI – PRHR Heat Removal Rate – 20 psi	15.6-165
15.6.5.4B-55	DEDVI – Integrated PRHR Heat Removal – 20 psi.....	15.6-166
15.6.5.4B-36A	DEDVI – Vessel Side Liquid Break Discharge – 14.7 psi	15.6-167
15.6.5.4B-37A	DEDVI – Vessel Side Vapor Break Discharge – 14.7 psi.....	15.6-168
15.6.5.4B-38A	DEDVI – RCS Pressure – 14.7 psi.....	15.6-169
15.6.5.4B-39A	DEDVI – Broken CMT Injection Rate – 14.7 psi	15.6-170
15.6.5.4B-40A	DEDVI – Intact CMT Injection Rate – 14.7 psi	15.6-171
15.6.5.4B-41A	DEDVI – Core/Upper Plenum Mixture Level – 14.7 psi	15.6-172
15.6.5.4B-42A	DEDVI – Downcomer Mixture Level – 14.7 psi	15.6-173
15.6.5.4B-43A	DEDVI – ADS 1-3 Vapor Discharge – 14.7 psi	15.6-174
15.6.5.4B-44A	DEDVI – Core Exit Void Fraction – 14.7 psi	15.6-175
15.6.5.4B-45A	DEDVI – Core Exit Liquid Flow Rate – 14.7 psi	15.6-176
15.6.5.4B-46A	DEDVI – Core Exit Vapor Flow Rate – 14.7 psi	15.6-177
15.6.5.4B-47A	DEDVI – Lower Plenum to Core Flow Rate – 14.7 psi	15.6-178
15.6.5.4B-48A	DEDVI – ADS-4 Liquid Discharge – 14.7 psi.....	15.6-179
15.6.5.4B-49A	DEDVI – ADS-4 Integrated Discharge – 14.7 psi	15.6-180
15.6.5.4B-50A	DEDVI – Intact Accumulator Flow Rate – 14.7 psi.....	15.6-181
15.6.5.4B-51A	DEDVI – Intact IRWST Injection Rate – 14.7 psi	15.6-182
15.6.5.4B-52A	DEDVI – Intact CMT Mixture Level – 14.7 psi	15.6-183
15.6.5.4B-53A	DEDVI – RCS System Inventory – 14.7 psi	15.6-184
15.6.5.4B-54A	DEDVI – PRHR Heat Removal Rate – 14.7 psi	15.6-185
15.6.5.4B-55A	DEDVI – Integrated PRHR Heat Removal – 14.7 psi.....	15.6-186
15.6.5.4B-56	10-Inch Cold Leg Break – RCS Pressure	15.6-187
15.6.5.4B-57	10-Inch Cold Leg Break – Pressurizer Mixture Level.....	15.6-188
15.6.5.4B-58	10-Inch Cold Leg Break – CMT-1 Mixture Level	15.6-189
15.6.5.4B-59	10-Inch Cold Leg Break – CMT-2 Mixture Level	15.6-190
15.6.5.4B-60	10-Inch Cold Leg Break – Downcomer Mixture Level.....	15.6-191
15.6.5.4B-61	10-Inch Cold Leg Break – CMT-1 Injection Rate	15.6-192
15.6.5.4B-62	10-Inch Cold Leg Break – CMT-2 Injection Rate	15.6-193
15.6.5.4B-63	10-Inch Cold Leg Break – Accumulator-1 Injection Rate	15.6-194
15.6.5.4B-64	10-Inch Cold Leg Break – Accumulator-2 Injection Rate	15.6-195
15.6.5.4B-65	10-Inch Cold Leg Break – IRWST-1 Injection Rate	15.6-196
15.6.5.4B-66	10-Inch Cold Leg Break – IRWST-2 Injection Rate	15.6-197
15.6.5.4B-67	10-Inch Cold Leg Break – ADS-4 Liquid Discharge	15.6-198
15.6.5.4B-68	10-Inch Cold Leg Break – RCS System Inventory.....	15.6-199
15.6.5.4B-69	10-Inch Cold Leg Break – Core/Upper Plenum Mixture Level.....	15.6-200

LIST OF FIGURES (Cont.)

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
15.6.5.4B-70	10-Inch Cold Leg Break – Composite Core Mixture Level.....	15.6-201
15.6.5.4B-71	10-Inch Cold Leg Break – Core Exit Liquid Flow	15.6-202
15.6.5.4B-72	10-Inch Cold Leg Break – Core Exit Vapor Flow.....	15.6-203
15.6.5.4B-73	10-Inch Cold Leg Break – Core Exit Void Fraction.....	15.6-204
15.6.5.4B-74	10-Inch Cold Leg Break – ADS-4 Integrated Discharge	15.6-205
15.6.5.4B-75	10-Inch Cold Leg Break – Liquid Break Discharge	15.6-206
15.6.5.4B-76	10-Inch Cold Leg Break – Vapor Break Discharge.....	15.6-207
15.6.5.4B-77	10-Inch Cold Leg Break – PRHR Heat Removal Rate.....	15.6-208
15.6.5.4B-78	10-Inch Cold Leg Break – Integrated PRHR Heat Removal	15.6-209
15.6.5.4B-79	DEDVI – Downcomer Pressure Comparison	15.6-210
15.6.5.4B-80	DEDVI – Intact IRWST Injection Flow.....	15.6-211
15.6.5.4B-81	DEDVI – Intact DVI Line Injection Flow.....	15.6-212
15.6.5.4B-82	DEDVI – ADS-4 Integrated Liquid Discharge Comparison	15.6-213
15.6.5.4B-83	DEDVI – Upper Plenum Mixture Mass Comparison.....	15.6-214
15.6.5.4B-84	DEDVI – ADS-4 Integrated Vapor Discharge Comparison	15.6-215
15.6.5.4B-85	DEDVI – Downcomer Region Mass Comparison.....	15.6-216
15.6.5.4B-86	DEDVI – Core Region Mass Comparison.....	15.6-217
15.6.5.4B-87	DEDVI – Vessel Mixture Mass Comparison	15.6-218
15.6.5.4B-88	DEDVI – Core/Upper Plenum Mixture Level Comparison	15.6-219
15.6.5.4B-89	DEDVI – Core Collapsed Liquid Level Comparison	15.6-220
15.6.5.4B-90	DEDVI – Pressurizer Mixture Level Comparison.....	15.6-221
15.6.5.4C-1	Collapsed Level of Liquid in the Downcomer (DEDVI Case)	15.6-222
15.6.5.4C-2	Collapsed Level of Liquid over the Heated Length of the Fuel (DEDVI Case)	15.6-223
15.6.5.4C-3	Void Fraction in Core Hot Assembly Top Cell (DEDVI Case).....	15.6-224
15.6.5.4C-4	Void Fraction in Core Hot Assembly Second from Top Cell (DEDVI Case)	15.6-225
15.6.5.4C-5	Collapsed Liquid Level in the Hot Leg of Pressurizer Loop (DEDVI Case).....	15.6-226
15.6.5.4C-6	Vapor Rate out of the Core (DEDVI Case).....	15.6-227
15.6.5.4C-7	Liquid Flow Rate out of the Core (DEDVI Case)	15.6-228
15.6.5.4C-8	Collapsed Liquid Level in the Upper Plenum (DEDVI Case).....	15.6-229
15.6.5.4C-9	Mixture Flow Rate Through ADS Stage 4A Valves (DEDVI Case).....	15.6-230
15.6.5.4C-10	Mixture Flow Rate Through ADS Stage 4B Valves (DEDVI Case).....	15.6-231
15.6.5.4C-11	Upper Plenum Pressure (DEDVI Case).....	15.6-232
15.6.5.4C-12	Peak Cladding Temperature (DEDVI Case).....	15.6-233
15.6.5.4C-13	DVI-A Mixture Flow Rate (DEDVI Case).....	15.6-234
15.6.5.4C-14	DVI-B Mixture Flow Rate (DEDVI Case)	15.6-235
15.6.5.4C-1A	Collapsed Level of Liquid in the Downcomer (DEDVI Case) – 14.7 psi	15.6-236
15.6.5.4C-2A	Collapsed Level of Liquid over the Heated Length of the Fuel (DEDVI Case) – 14.7 psi	15.6-237
15.6.5.4C-3A	Void Fraction in Core Hot Assembly Top Cell (DEDVI Case) – 14.7 psi	15.6-238
15.6.5.4C-4A	Void Fraction in Core Hot Assembly Second from Top Cell (DEDVI Case) – 14.7 psi.....	15.6-239
15.6.5.4C-5A	Collapsed Liquid Level in the Hot Leg of Pressurizer Loop (DEDVI Case) – 14.7 psi	15.6-240

LIST OF FIGURES (Cont.)

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
15.6.5.4C-6A	Vapor Rate out of the Core (DEDVI Case) – 14.7 psi	15.6-241
15.6.5.4C-7A	Liquid Flow Rate out of the Core (DEDVI Case) – 14.7 psi.....	15.6-242
15.6.5.4C-8A	Collapsed Liquid Level in the Upper Plenum (DEDVI Case) – 14.7 psi	15.6-243
15.6.5.4C-9A	Mixture Flow Rate Through ADS Stage 4A Valves (DEDVI Case) – 14.7 psi	15.6-244
15.6.5.4C-10A	Mixture Flow Rate Through ADS Stage 4B Valves (DEDVI Case) – 14.7 psi	15.6-245
15.6.5.4C-11A	Upper Plenum Pressure (DEDVI Case) – 14.7 psi	15.6-246
15.6.5.4C-12A	Peak Cladding Temperature (DEDVI Case) – 14.7 psi	15.6-247
15.6.5.4C-13A	DVI-A Mixture Flow Rate (DEDVI Case) – 14.7 psi	15.6-248
15.6.5.4C-14A	DVI-B Mixture Flow Rate (DEDVI Case) – 14.7 psi	15.6-249
15.6.5.4C-15	Collapsed Level of Liquid in the Downcomer (Wall-to-Wall Floodup Case) – 14.7 psi	15.6-250
15.6.5.4C-16	Collapsed Level of Liquid Over the Heated Length of the Fuel (Wall-to-Wall Floodup Case) – 14.7 psi.....	15.6-251
15.6.5.4C-17	Void Fraction in Core Hot Assembly Top Cell (Wall-to-Wall Floodup Case) – 14.7 psi	15.6-252
15.6.5.4C-18	Void Fraction in Core Hot Assembly Second from Top Cell (Wall-to-Wall Floodup Case) – 14.7 psi	15.6-253
15.6.5.4C-19	Collapsed Liquid Level in the Hot Leg of Pressurizer Loop (Wall-to-Wall Floodup Case) – 14.7 psi.....	15.6-254
15.6.5.4C-20	Vapor Rate out of the Core (Wall-to-Wall Floodup Case) – 14.7 psi.....	15.6-255
15.6.5.4C-21	Liquid Flow Rate out of the Core (Wall-to-Wall Floodup Case) – 14.7 psi.....	15.6-256
15.6.5.4C-22	Collapsed Liquid Level in the Upper Plenum (Wall-to-Wall Floodup Case) – 14.7 psi	15.6-257
15.6.5.4C-23	Mixture Flow Rate Through ADS Stage 4A Valves (Wall-to-Wall Floodup Case) – 14.7 psi.....	15.6-258
15.6.5.4C-24	Mixture Flow Rate Through ADS Stage 4B Valves (Wall-to-Wall Floodup Case) – 14.7 psi.....	15.6-259
15.6.5.4C-25	Upper Plenum Pressure (Wall-to-Wall Floodup Case) – 14.7 psi	15.6-260
15.6.5.4C-26	Hot Rod Cladding Temperature Near Top of Core (Wall-to-Wall Floodup Case) – 14.7 psi.....	15.6-261
15.6.5.4C-27	DVI-A Mixture Flow Rate (Wall-to-Wall Floodup Case) – 14.7 psi.....	15.6-262
15.6.5.4C-28	DVI-B Mixture Flow Rate (Wall-to-Wall Floodup Case) – 14.7 psi	15.6-263
15A-1	Site Plan With Release and Intake Locations	15A-18